



**INTERNATIONAL STANDARD ISO/IEC 11582:1995**  
**TECHNICAL CORRIGENDUM 1**

Published 1999-12-01

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION  
INTERNATIONAL ELECTROTECHNICAL COMMISSION • МЕЖДУНАРОДНАЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ • COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

**Information technology — Telecommunications and  
information exchange between systems — Private  
Integrated Services Network — Generic functional protocol  
for the support of supplementary services —  
Inter-exchange signalling procedures and protocol**

**TECHNICAL CORRIGENDUM 1**

*Technologies de l'information — Télécommunications et échange d'information entre systèmes — Réseau privé à  
intégration de services — Protocole générique fonctionnel pour le support de compléments de service —  
Procédures et protocole de signalisation entre commutateurs*

**RECTIFICATIF TECHNIQUE 1**

Technical Corrigendum 1 to International Standard ISO/IEC 11582:1995 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*.

*Page 1, Clause 1:*

In the third line of NOTE 1: "Annex A" is replaced by "Annex C".

*Page 1, Clause 3:*

A new reference is added as follows:

"ISO/IEC 11571:1992, *Information technology - Telecommunications and information exchange between systems - Numbering and sub-addressing in private integrated services networks*."

Page 3, Subclause 4.29:

Add a new subclause after 4.29 (and renumber all subsequent subclauses in clause 4) as follows:

“4.30 PINX address

A PISN number as defined in ISO/IEC 11571 that is a complete number and that unambiguously identifies the addressed PINX or an addressable entity associated with that PINX.”

Page 9, Subclause 7.1.1.1:

The second paragraph which begins with "Three exceptions where the Facility information element shall not be sent and an indication... " is replaced with the following:

"Four exceptions where the Facility information element shall not be sent in a FACILITY message and an indication...".

Page 10, Table 10, 2<sup>nd</sup> column, last line (Case No 6):

"addressed PINX" is replaced by "Next PINX".

Page 11, Subclause 7.1.2.4:

The first paragraph is modified to read “Figures 4 to 7 show SDL diagrams .... “

Page 19, Table 11, 1<sup>st</sup> and 2<sup>nd</sup> line (T303):

In the 5<sup>th</sup> column (Normally terminated) the message CONNECT is deleted.

Page 19, Table 12, add the following two rows to the bottom of the table:

PC_	Primitives from / to GFT Control to / from Protocol Control.
DL_	Primitives from / to the SCM to / from Protocol Control.

Page 32, Subclause 7.3.3.3.1:

A new note is added after the first paragraph as follows:

“NOTE – Before sending the CONNECT message, GFT Control should determine from the coordination function if any APDUs are to be included in the CONNECT message.”

Page 42, Subclause 10.3:

A new NOTE is added after Table 17 as follows:

"NOTE– In case of the establishment of a Call Independent Signalling Connection the following information elements are not included:

Channel identification  
Connected subaddress,  
Notification indicator,  
Low layer compatibility,  
Progress indicator"