

---

---

**Agricultural tractor drive wheel  
tyres — Explanation of rolling  
circumference index (RCI) and speed  
radius index (SRI) and method of  
measuring tyre rolling circumference**

*Pneumatiques pour roues motrices de tracteurs agricoles —  
Explication de l'indice de circonférence de roulement (RCI) et de  
l'indice de rayon de roulement (SRI) et de la méthode de mesure de la  
circonférence de roulement*



STANDARDSISO.COM : Click to view the full PDF of ISO 11795:2018



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Fax: +41 22 749 09 47  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
Foreword.....	iv
Introduction.....	v
<b>1 Scope.....</b>	<b>1</b>
<b>2 Normative references.....</b>	<b>1</b>
<b>3 Terms and definitions.....</b>	<b>1</b>
<b>4 Principle.....</b>	<b>1</b>
<b>5 Test conditions.....</b>	<b>2</b>
5.1 Tyre installation.....	2
5.2 Test tyres.....	2
5.3 Tyre load and inflation pressure.....	2
5.4 Tyre measurement.....	2
5.5 Test course.....	2
5.6 Weather conditions.....	2
5.7 Test measurement.....	2
5.8 Test speed.....	2
<b>6 Method of test.....</b>	<b>2</b>
6.1 Test preparation.....	2
6.2 Test procedure.....	3
<b>7 Expression of results.....</b>	<b>3</b>
<b>8 Test report.....</b>	<b>3</b>
<b>9 Other test conditions.....</b>	<b>3</b>
<b>10 Rolling circumference index (RCI).....</b>	<b>4</b>
<b>11 Speed radius index (SRI).....</b>	<b>5</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 31, *Tyres, rims and valves*, Subcommittee SC 5, *Agricultural tyres and rims*.

This second edition cancels and replaces the first edition (ISO 11795:1997), which has been technically revised. It also incorporates the Amendment ISO 11795:1997/Amd.1:2010.

## Introduction

Matching front and rear wheels with different tyre sizes on four-wheel drive agricultural tractors requires accurate rolling circumference values. The test method to determine rolling circumference outlined in this document was developed to follow this requirement. The values thus obtained are not intended for use as levels of performance or quality.

The test speed has been set at typical working speed when the four-wheel drive will likely be engaged and the most critical match is required. Generally, the four-wheel drive is disengaged at road speeds. Therefore, the determination of rolling circumference is not related to the tyre's maximum speed, e.g. 30 km/h or 40 km/h. Nevertheless, other speeds or conditions may be run provided it is clearly documented in the results.

STANDARDSISO.COM : Click to view the full PDF of ISO 11795:2018

STANDARDSISO.COM : Click to view the full PDF of ISO 11795:2018

# Agricultural tractor drive wheel tyres — Explanation of rolling circumference index (RCI) and speed radius index (SRI) and method of measuring tyre rolling circumference

## 1 Scope

This document specifies the method for measuring rolling circumference for new tyres, under loaded conditions, made for use on agricultural tractors and machines, and applies to agricultural tractor drive wheel tyres in diagonal and radial construction. It also includes an explanation of the rolling circumference index (RCI) and speed radius index (SRI).

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4251-1, *Tyres (ply rating marked series) and rims for agricultural tractors and machines — Part 1: Tyre designation and dimensions, and approved rim contours*

ISO 4251-2, *Tyres (ply rating marked series) and rims for agricultural tractors and machines — Part 2: Tyre load ratings*

ISO 7867-1, *Metric series for agricultural, forestry machines and construction tyres — Part 1: Tyre designation, dimensions and marking, and tyre/rim coordination*

ISO 7867-2, *Metric series for agricultural, forestry machines and construction tyres — Part 2: Load ratings for agricultural tyres*

ISO 8664, *Tyres for agricultural tractors and machines — Code-designated and service-description marked radial drive-wheel tyres*

## 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

### 3.1

#### rolling circumference of tyre

distance that the (axle) centre of the tyre moves in one revolution of the tyre under specified conditions

Note 1 to entry: Test conditions are specified in [Clause 5](#).

## 4 Principle

The measurement consists of driving a typical vehicle equipped with the test tyres on the drive axle, on a straight, level road at a constant speed, and counting the number of tyre revolutions (or portions thereof) that occur while traversing a measured distance.

## 5 Test conditions

### 5.1 Tyre installation

Tyre to be tested shall be installed as a single on the drive wheels of a vehicle which shall be representative of that used with the tyre size being tested. An approved rim in accordance with ISO 4251-1, ISO 7867-1 or ISO 8664 shall be used.

Only the test axle shall be driven.

### 5.2 Test tyres

The tyres shall be a matched set of the same size designation, type, and brand, having inflated, unloaded overall diameters within 0,5 % of each other.

### 5.3 Tyre load and inflation pressure

The load on each tyre shall be the maximum rated load stamped on the tyre sidewall, in accordance with ISO 4251-2, ISO 7867-2 or ISO 8664. Tyre inflation pressure shall be the reference inflation pressure that corresponds to the 30 km/h load. The tyre shall be inflated with air only.

### 5.4 Tyre measurement

The overall diameter of each tyre shall be measured after being inflated for 24 h at ambient temperature with no applied load and the inflation pressure specified in 5.3. Inflation pressure shall be checked and adjusted, if necessary, immediately prior to measurement.

### 5.5 Test course

The test course for the distance specified in [Clause 6](#) shall be a level, straight section of flat, dry road surface (asphalt or concrete).

### 5.6 Weather conditions

The ambient air temperature for measuring, warm-up, and test shall be between 5 °C and 30 °C; however, an asphaltic surface shall be sufficiently cool that the surface is not tacky. The wind speed shall not exceed 15 km/h.

### 5.7 Test measurement

Distance shall be determined by direct measurement or by tyre use of a calibrated fifth wheel. Each tyre on test shall be instrumented to return a minimum of eight impulses per revolution.

### 5.8 Test speed

Tyres shall be tested at 10 km/h  $\pm$  2 km/h.

## 6 Method of test

### 6.1 Test preparation

Immediately prior to testing, the inflation pressure of the loaded tyres shall be adjusted to the inflation pressure specified in 5.3 at the ambient temperature. Tyres shall be run for 30 min at 25 km/h  $\pm$  5 km/h or until inflation pressure stabilizes (warm-up). The inflation pressure shall not be readjusted afterwards.



## 6.2 Test procedure

Immediately after the test preparation, run the test at the speed specified in 5.8 to achieve a minimum of 1 000 impulses over a test course of 100 m minimum while recording the number of impulses for the right wheel and the left wheel separately. During the test run, a differential lock shall not be engaged, acceleration and braking shall be avoided and steering input should be kept to minimum. Two runs shall be made in each direction of travel on the test course. Repeat this procedure if the number of impulses recorded on any run differs from the others by more than 0,2 %.

In the event of stoppage or interruption of the test, repeat the whole test.

## 7 Expression of results

The tyre rolling circumference is calculated by averaging the impulses recorded for the eight observations per test (4 runs × 2 tyres) and then using [Formula \(1\)](#):

$$RC = \frac{1\,000 \times S \times ipr}{n} \quad (1)$$

where

$RC$  is the rolling circumference, in millimetres;

$S$  is the test course length, in metres;

$ipr$  is the number of impulses per tyre revolution;

$n$  is the average number of impulses recorded per test.

## 8 Test report

The test report shall include the following information:

- a) a reference to this document, i.e. ISO 11795:2018;
- b) the identification of the tested tyre (tyre size designation and service description);
- c) the rim width code;
- d) the tyre overall diameter (mm);
- e) the tyre load (kg);
- f) the inflation pressure (kPa);
- g) the ambient air temperature (°C);
- h) the test speed (km/h);
- i) the test distance (m);
- j) the test result (rolling circumference in mm);
- k) the date of the test (year-month-day).

## 9 Other test conditions

If desired and agreed upon among the interested parties, rolling circumference under other conditions may be determined by following the above method of test. The test report shall clearly indicate that results were obtained under non-standard conditions which shall be defined.