
**Motorcycle tyres and rims
(code-designated series) —**

**Part 3:
Rims**

*Pneumatiques et jantes pour motocycles (séries dont les dimensions
sont désignées par des codes) —*

Partie 3: Jantes



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 4249-3:2010



COPYRIGHT PROTECTED DOCUMENT

© ISO 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Finish	1
3.1 Rim contour	1
3.2 Rim valve hole	1
4 Designation	3
5 Cylindrical bead seat	3
5.1 Rim contours	3
5.2 Rim diameters	4
6 Tapered bead seat rims (MT type)	4
6.1 Rim contours	4
6.2 Bead seat contours	6
6.3 Rim diameter and hump circumference	7
7 Permitted rim widths	7
Annex A (informative) Rim circumference measurement — Tapered bead seat (MT type) rims	9
Bibliography	11

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 4249-3 was prepared by Technical Committee ISO/TC 31, *Tyres, rims and valves*, Subcommittee SC 10, *Cycle, moped, motorcycle tyres and rims*.

This sixth edition cancels and replaces the fifth edition (ISO 4249-3:2004), which has been technically revised.

ISO 4249 consists of the following parts, under the general title *Motorcycle tyres and rims (code-designated series)*:

- *Part 1: Tyres*
- *Part 2: Tyre load ratings*
- *Part 3: Rims*

Motorcycle tyres and rims (code-designated series) —

Part 3: Rims

1 Scope

This part of ISO 4249 specifies the rim dimensions for a selection of rims for motorcycle tyres. It stipulates only those rim contour dimensions necessary for tyre mounting, and for fitting the tyre to the rim.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4249-1:1985, *Motorcycle tyres and rims (Code-designated series) — Part 1: Tyres*

3 Finish

3.1 Rim contour

The rim on the side of the tyre shall be smoothly contoured and free of sharp edges.

3.2 Rim valve hole

3.2.1 The rim valve hole shall be centred on the bottom of the rim well. On the tyre side, the edges shall be rounded or chamfered. On the hub side, the edges shall be free of burrs, which could damage the valve.

Dimensions and tolerances of valve holes shall be as shown in Figure 1.

3.2.2 The rim hole shall have a diameter of $8,3^{+0,5}_{-0,1}$ mm. See Figure 1 a).


For the fitment of tubeless valves, a circumferential flat area of at least 14,5 mm is required on the tyre side of the rim. The maximum thickness of the rim at the rim hole shall be 9,4 mm. See Figure 1 b).

At the request of the motorcycle manufacturer, rim holes of $11,3^{+0,4}_0$ mm diameter may be provided; in this case, the flat area around the hole shall be at least 19 mm diameter.

For the possibility of off-centre positioning, see Figure 1 c).

3.2.3 The rim shall be counter-bored at the valve hole to reduce the thickness to 4 mm maximum for seating snap-in valves.

Dimensions in millimetres



a Optional.

b See 3.2.3.

c For rim codes MT 3.00 and larger, if the well contour offers sufficient space for the location of the flat area, the valve hole may be positioned on the sidewall of the well.

Figure 1 — Valve hole dimensions


4 Designation

The rim shall be designated by its nominal rim diameter code and nominal rim width (for example, 18 × 1.85 or 17 M/C × MT 3.50). See also ISO 3911.

5 Cylindrical bead seat

5.1 Rim contours

Dimensions and tolerances of the cylindrical bead seat rims shall be as shown in Figure 2 and as given in Table 1.



^a See Table 2.

Figure 2 — Cylindrical bead seat rims

Table 1 — Dimensions of cylindrical bead seat rims

Dimensions in millimetres

Nominal rim width	A	B	G	H	P	C	R ₂	R ₁	R ₃	R ₄	R ₅		
inches	⁺¹ _{-0,5}	min.	± 0,5	⁺¹ _{-0,5}	min.			min.	max.	min.	min.		
1.10	28	5	7	7	3	5	5,5	1,5	1,5	5	7		
1.20	30,5	5,5	9			5,5	6						
1.35	34	6,5	10	7,5	3,5	6	6,5	2		2	5,5	11,5	
1.40	36			8								4	6,5
1.50	38	7,5	10,5	9	4,5	7,5	8		6		15		
1.60	40,5		12		10,5	12,5	3				3	7	19
1.85	47	8,5	14						5				
2.15	55								7,5				
2.50	63,5	9,5			12	11							
2.75	70	10,5											
3.00	76												

5.2 Rim diameters

Nominal rim diameter code, specified diameters and circumferences shall be as given in Table 2.

Table 2 — Specified rim diameters and circumferences for cylindrical bead seat rims

Dimensions in millimetres

Nominal rim diameter code ^a	Specified rim diameter <i>D</i>	Specified rim circumference πD ⁺² _{-0,5}
14	357,1	1 121,9
15	382,5	1 201,7
16	405,6	1 274,2
17	433,3	1 361,2
18	458,7	1 441
19	484,1	1 520,8
20	509,5	1 600,6
21	534,9	1 680,4
22	558,8	1 755,5
23	584,2	1 835,3


^a The suffix M/C is optionally allowed.

6 Tapered bead seat rims (MT type)

6.1 Rim contours

Dimensions and tolerances of tapered bead seat rims shall be as shown in Figure 3 and as given in Table 3.

The well contours of MT 2.50 and wider rims, however, are permitted to be between those shown in Figure 3 (basic contours) and Figure 4.



$\alpha = 22^\circ \substack{0 \\ -5}$ (see Table 3, footnote d).

NOTE For *D* and *D_H*, see 6.3.

Figure 3 — 5° tapered bead seat rim contours (MT type)

Table 3 — Dimensions of tapered bead seat rims

Dimensions in millimetres


Nominal rim width code	A		B	C	E ^a		G		H	R ₁	R ₂	R ₃	R ₄	R ₅ ^b	R ₆	R ₇
		tol.	min.			tol.		tol.	min.	min.		max.	± 0,5	min.	± 0,5	± 0,5
MT 1.50	38	+1 -0,5	7,5	6,5	—	—	10	± 0,5	8	3	7	2,5	—	3	—	—
MT 1.60	40,5		9	8,5	10	+0,5 0	12		9		12,5	2,5	3		2,5	
MT 1.85	47			10,5	12 ^c		14	5,5								
MT 2.15	55		13		+2 0	12			13							
MT 2.50	63,5	14		+1 -0,5			12	13								
MT 2.75	70		15		13	12			13							
MT 3.00	76	16		13			12	13								
MT 3.50	89		16		13	12			13							
MT 3.75	95	16		13			12	13								
MT 4.00	101,5		16		13	12			13							
MT 4.25	108	16		13			12	13								
MT 4.50	114,5		16		13	12			13							
MT 5.00	127	16		13			12	13								
MT 5.50	140		16		13	12			13							
MT 6.00	152,5	16		13			12	13								
MT 6.25	159		16		13	12			13							
MT 6.50	165	16		13			12	13								
MT 7.00	178		16		13	12			13							
MT 7.50	190,5	16		13			12	13								
MT 8.00	203		16		13	12			13							
MT 8.50	216	16		13			12	13								
MT 9.00	228,5		16		13	12			13							
MT 9.50	241,5	16		13			12	13								
MT 10.00	254		16		13	12			13							
MT 10.50	266,5	16		13			12	13								
MT 11.00	279,5		16		13	12			13							
MT 11.50	292	16		13			12	13								
MT 12.00	305		16		13	12			13							
MT 12.50	317,5	16		13			12	13								
MT 13.00	330		16		13	12			13							
MT 13.50	343	16		13			12	13								

^a E = hump location. See Figure 5 and Table 4 for rims without humps.

^b For MT 2.50 and larger rims, the well contour may be a rounded shape with R = full radius. See Option 1, Figure 4.

^c For MT 1.85, 10,5^{+0,5}₋₀ is also permitted for better tyre mounting.

^d 5 ± 0,5 of R₄ for MT 2.15 is also permitted. In that case, α shall be 17° ± 2,5°.



Key
R full radius

Figure 4 — Well contour — Option 1

6.2 Bead seat contours

Bead seat contours for rims without hump shall be as shown in Figure 5 and as given in Table 4.

Rims without hump shall only be used with tyres for tube-type applications.




Figure 5 — Bead seat contours for rims without hump

Table 4 — Bead seat contours for rims without hump

Dimensions in millimetres

Nominal rim width code	<i>P</i>
	+2 0
MT 1.50	4
MT 1.60	5
MT 1.85	8
MT 2.15	11

6.3 Rim diameter and hump circumference

The nominal rim diameter code, specified rim diameter and hump circumference shall be as given in Table 5.

Annex A provides a procedure that may be used for determining the measuring rim diameter and the measuring rim circumference when an 8 mm ball tape is used for checking MT rims.

Table 5 — Specified rim diameters and hump circumferences for MT rim contours

Dimensions in millimetres

Nominal rim diameter code	Specified rim diameter ^a D	Hump circumference πD_H $\begin{smallmatrix} +2 \\ -1 \end{smallmatrix}$
13 M/C	332,2	1 041,5
14 M/C	357,6	1 121,3
15 M/C	383	1 201,1
16 M/C	406	1 273,4 ^b
17 M/C	433,8	1 360,7
18 M/C	459,2	1 440,5
19 M/C	484,6	1 520,3
20 M/C	510	1 600,1
21 M/C	535,4	1 679,9
23 M/C	586,2	1 839,5
24 M/C	611,6	1 919,3
NOTE The suffix M/C for nominal rim diameter codes 16 M/C and above is optional for rims manufactured before May 2003.		
^a The tolerance on the bead seat periphery is $\begin{smallmatrix} +1,5 \\ -0,5 \end{smallmatrix}$ mm.		
^b For code 16 M/C, the tolerance on the bead seat periphery is ± 1 mm.		

7 Permitted rim widths

Permitted rim widths for the code-designated series of motorcycle tyres shall be in accordance with Table 6.

NOTE For permitted rim widths for the metric series of motorcycle tyres, see ISO 5751-3.

Table 6 — Permitted rim widths

Tyre section	Permitted rim widths ^a
2.00	1.10; 1.20; 1.35
2.25	1.20; 1.35; 1.40; 1.50; 1.60
2.50	1.35; 1.40; 1.50; 1.60
2.75	1.40; 1.50; 1.60; 1.85
3.00	1.60; 1.85; 2.15
3.25	1.85; 2.15; 2.50
3.50	1.85; 2.15; 2.50
3.75	1.85; 2.15; 2.50
4.00	2.15; 2.50; 2.75; 3.00
4.25	2.15; 2.50; 2.75; 3.00
4.50	2.15; 2.50; 2.75; 3.00
5.00	2.50; 2.75; 3.00; 3.50

^a MT contours may also apply. The measuring rim width for a given tyre section shall be obtained in accordance with ISO 4249-1:1985, Table 3.