

AEROSPACE MATERIAL SPECIFICATION

SAE

AMS 3856/1A

Issued 1 JAN 1985 Revised 1 JAN 1993 Superseding AMS 3856/1

Submitted for recognition as an American National Standard

CLOTH, UPHOLSTERY, FLAME RESISTANT Novoloid/Aramid, Waffle Type Weave

This specification has been declared "NONCURRENT" by the Aerospace Materials Division, SAE, as of July, 1992. It is recommended, therefore, that this specification not be specified for new designs.

This cover sheet should be attached to the initial issue of the subject specification.

"NONCURRENT" refers to those materials which have previously been widely used and which may be required on some existing designs in the future. The Aerospace Materials Division, however, does not recommend these as standard materials for future use in new designs. Each of these "NONCURRENT" specifications is available from SAE upon request.

PREPARED UNDER THE JURISDICTION OF AMS COMMITTEE "CP".

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.



400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE MATERIAL SPECIFICATION

AMS 3856/1

Issued Revised 1-1-85

CLOTH, UPHOLSTERY, FLAME RESISTANT Novoloid/Aramid, Waffle Type Weave

- 1. <u>SCOPE:</u>
- 1.1 Form: This specification covers one weight and one weave of novoloid/aramid cloth.
- 1.2 Application: Primarily for use in upholstering arcraft seats.
- 1.3 <u>Classification</u>: Novoloid/aramid cloth with a honeycomb or waffle type weave.
- 2. APPLICABLE DOCUMENTS: See AMS 3856.
- 3. TECHNICAL REQUIREMENTS:
- 3.1 <u>Basic Specification:</u> The complete requirements for procuring the cloth described herein shall consist of this document and the latest issue of the basic specification, AMS 3856.
- 3.2 Construction: Shall be as follows:
- 3.2.1 Yarn: Warp yarns used in weaving the cloth shall be singles and two ply, 50/50 staple fiber blend of aramid and novoloid, and two ply, 100% aramid. Filling yarn shall be singles and two ply, 50/50 staple fiber blend of aramid and novoloid.
- 3.2.2 Cloth:
- 3.2.2.1 Weave: Shall be honeycomb or waffle type.
- 3.2.2.2 Color: Shall be natural. (The novoloid fiber is a tan color.)
- 3.2.2.3 Width: Shall be 54 in. (1,350 mm) exclusive of selvages.

SAE Technical Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

AMS documents are protected under United States and international copyright laws. Reproduction of these documents by any means is strictly prohibited without the written consent of the publisher.