


REV.
A

AS1656

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.




(R) FIGURE 1 - FERRULE END

(R) TABLE 1 - FERRULE END DIMENSIONS /4/

BASIC NUMBER AS1656-1 SIZE CODE	TUBE SIZE (REF)	A ±.003	B ±.003	C ±.005	D MACH END ±.0025	D CAST END ±.005	E ±.005	F ±.002	G ±.002
-05	.312	.479	.406	.125	.0375	.050	.090	.375	.476
-06	.375	.541	.468	.125	.0375	.050	.090	.437	.538
-08	.500	.686	.622	.130	.0375	.050	.090	.581	.682
-10	.625	.811	.747	.130	.0375	.050	.090	.706	.807
-12	.750	.991	.887	.165	.0425	.065	.125	.838	.987
-16	1.000	1.267	1.139	.205	.0425	.065	.165	1.060	1.263
-20	1.250	1.517	1.389	.205	.0425	.065	.165	1.310	1.513
-24	1.500	1.787	1.639	.205	.0425	.065	.165	1.580	1.783
-28	1.750	2.037	1.889	.205	.0425	.065	.165	1.830	2.033
-32	2.000	2.310	2.142	.205	.0575	.080	.165	2.093	2.306
-36	2.250	2.560	2.392	.205	.0575	.080	.165	2.345	2.556
-40	2.500	2.810	2.642	.205	.0575	.080	.165	2.593	2.806
-48	3.000	3.310	3.142	.205	.0575	.080	.165	3.093	3.306
-56	3.500	3.822	3.642	.205	.0575	.080	.165	3.605	3.818
-64	4.000	4.328	4.151	.205	.0725	.095	.165	4.114	4.324

THIRD ANGLE PROJECTION



CUSTODIAN: SAE G-3/G-3A

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space
INTERNATIONAL

400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD

FITTING END, THREADLESS COUPLING -
FERRULE OR SLEEVE, DESIGN STANDARD


AS1656

SHEET 1 OF 4

REV.**A**

REV.
A

AS1656



(R) FIGURE 2 - SLEEVE END

(R) TABLE 2 - SLEEVE END DIMENSIONS /4/

BASIC NUMBER AS1656-2 SIZE CODE	TUBE SIZE (REF)	H ±.004	J ±.010	K ±.003	L ±.003	M ±.002	N ±2°	P ±.010	R ±.005
-05	.312	.555	.461	.588	.406	.485	35	.428	.445
-06	.375	.617	.461	.588	.468	.547	35	.428	.507
-08	.500	.762	.471	.598	.622	.692	35	.433	.652
-10	.625	.887	.471	.598	.747	.817	35	.433	.777
-12	.750	1.067	.551	.678	.887	.997	35	.473	.957
-16	1.000	1.343	.631	.758	1.139	1.273	30	.513	1.233
-20	1.250	1.593	.631	.758	1.389	1.523	30	.513	1.483
-24	1.500	1.863	.631	.758	1.639	1.793	30	.513	1.753
-28	1.750	2.114	.631	.758	1.889	2.044	30	.513	2.004
-32	2.000	2.387	.661	.788	2.142	2.317	30	.528	2.277
-36	2.250	2.637	.661	.788	2.392	2.567	30	.528	2.527
-40	2.500	2.887	.661	.788	2.642	2.817	30	.528	2.777
-48	3.000	3.387	.661	.788	3.142	3.317	30	.528	3.277
-56	3.500	3.901	.661	.788	3.642	3.831	30	.528	3.791
-64	4.000	4.407	.661	.788	4.151	4.337	30	.543	4.297

REV.
A

AS1656




FIGURE 3 - SLEEVE END (FOR HOSE ENDS ONLY)

TABLE 3 - SLEEVE END DIMENSIONS FOR HOSE ENDS /4/

BASIC NUMBER AS1656-3 SIZE CODE	TUBE SIZE (REF)	H ±.004	J ±.010	K ±.003	L ±.003	M ±.002	N ±2°	R ±.005	S ±.010
-05	.312	.555	.461	.588	.406	.485	35	.445	.178
-06	.375	.617	.461	.588	.468	.547	35	.507	.178
-08	.500	.762	.471	.598	.622	.692	35	.652	.183
-10	.625	.887	.471	.598	.747	.817	35	.777	.183
-12	.750	1.067	.551	.678	.887	.997	35	.957	.233
-16	1.000	1.343	.631	.758	1.139	1.273	30	1.233	.273
-20	1.250	1.593	.631	.758	1.389	1.523	30	1.483	.273
-24	1.500	1.863	.631	.758	1.639	1.793	30	1.753	.273
-28	1.750	2.114	.631	.758	1.889	2.044	30	2.004	.273
-32	2.000	2.387	.661	.788	2.142	2.317	30	2.277	.288
-36	2.250	2.637	.661	.788	2.392	2.567	30	2.527	.288
-40	2.500	2.887	.661	.788	2.642	2.817	30	2.777	.288
-48	3.000	3.387	.661	.788	3.142	3.317	30	3.277	.288
-56	3.500	3.901	.661	.788	3.642	3.831	30	3.791	.288
-64	4.000	4.407	.661	.788	4.151	4.337	30	4.297	.303

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space
INTERNATIONAL

400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD

FITTING END, THREADLESS COUPLING -
FERRULE OR SLEEVE, DESIGN STANDARD

AS1656

SHEET 3 OF 4

REV.
A