

AS3255

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.





FIGURE 1

THIRD ANGLE PROJECTION



PREPARED BY SAE COMMITTEE E-25, GENERAL STANDARDS FOR AEROSPACE PROPULSION SYSTEMS

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space®
INTERNATIONAL
400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD

BOLT, MACHINE-DOUBLE HEX EXTENDED
WASHER HEAD, DRILLED, PD SHANK, SILVER PLATED
.5000-20 UNJF-3A

AS3255
SHEET 1 OF 3

REV.
A

REV.
A

AS3255

TABLE 1

PART NUMBER	L		G MIN		K MAX		APPROX. MASS	
	INCH	mm	INCH	mm	INCH	mm	LB/100	kg/100
AS3255-03	.740-.760	18.80-19.30	.030	0.77	.125	3.17	7.33	3.324
AS3255-04	.802-.822	20.38-20.87	.030	0.77	.125	3.17	7.65	3.470
AS3255-05	.865-.885	21.98-22.47	.030	0.77	.125	3.17	7.97	3.616
AS3255-06	.928-.948	23.58-24.07	.030	0.77	.125	3.17	8.29	3.762
AS3255-07	.990-1.010	25.15-25.65	.030	0.77	.125	3.17	8.61	3.903
AS3255-08	1.052-1.072	26.73-27.22	.030	0.77	.125	3.17	8.93	4.049
AS3255-09	1.115-1.135	28.33-28.82	.030	0.77	.125	3.17	9.25	4.195
AS3255-10	1.178-1.198	29.93-30.42	.030	0.77	.125	3.17	9.56	4.336
AS3255-11	1.240-1.260	31.50-32.00	.030	0.77	.125	3.17	9.88	4.482
AS3255-12	1.302-1.322	33.08-33.57	.030	0.77	.125	3.17	10.20	4.628
AS3255-13	1.365-1.385	34.68-35.17	.030	0.77	.125	3.17	10.53	4.774
AS3255-14	1.428-1.448	36.28-36.77	.030	0.77	.188	4.77	10.84	4.915
AS3255-15	1.490-1.510	37.85-38.35	.090	2.29	.250	6.35	11.16	5.061
AS3255-16	1.552-1.572	39.43-39.92	.152	3.87	.312	7.92	11.48	5.207
AS3255-17	1.615-1.635	41.03-41.52	.215	5.47	.375	9.52	11.80	5.353
AS3255-18	1.678-1.693	42.63-43.12	.278	7.07	.438	11.52	12.11	5.495
AS3255-19	1.740-1.760	44.20-44.70	.340	8.64	.500	12.70	12.44	5.641
AS3255-20	1.802-1.822	45.78-46.27	.402	10.22	.562	14.22	12.77	5.786
AS3255-21	1.865-1.885	47.38-47.87	.465	11.82	.625	15.87	13.07	5.928
AS3255-22	1.928-1.948	48.98-49.47	.528	13.42	.688	17.47	13.39	6.074
AS3255-23	1.990-2.010	50.55-51.05	.590	14.99	.750	19.05	13.71	6.220
AS3255-24	2.115-2.135	53.73-54.22	.715	18.17	.875	22.22	14.35	6.507
AS3255-25	2.240-2.260	56.90-57.40	.840	21.34	1.000	25.40	14.99	6.799
AS3255-26	2.365-2.385	60.08-60.57	.965	24.52	1.125	28.57	15.62	7.086
AS3255-27	2.490-2.510	63.25-63.75	1.090	27.69	1.250	31.75	16.27	7.378
AS3255-28	2.615-2.635	66.43-66.92	1.215	30.87	1.375	34.92	16.90	7.665
AS3255-29	2.740-2.760	69.60-70.10	1.340	34.04	1.500	38.10	17.54	7.957
AS3255-30	2.865-2.885	72.78-73.27	1.465	37.22	1.625	41.27	18.18	8.244
AS3255-31	2.990-3.010	75.95-76.45	1.590	40.39	1.750	44.45	18.81	8.244
AS3255-32	3.115-3.135	79.13-79.62	1.715	43.57	1.875	47.62	19.45	8.823
AS3255-33	3.240-3.260	82.30-82.80	1.840	46.74	2.000	50.80	20.09	9.111
AS3255-34	3.365-3.385	85.48-85.97	1.965	49.92	2.125	53.97	20.73	9.402
AS3255-35	3.490-3.510	88.65-89.15	2.090	53.09	2.250	57.15	21.36	9.690
AS3255-36	3.615-3.635	91.83-92.32	2.215	56.27	2.375	60.32	22.01	9.982
AS3255-37	3.740-3.760	95.00-95.50	2.340	59.44	2.500	63.60	22.64	10.269
AS3255-38	3.865-3.885	98.18-98.67	2.465	62.62	2.625	66.67	23.28	10.561
AS3255-39	3.990-4.010	101.35-101.85	2.590	65.79	2.750	69.85	23.92	10.848
AS3255-40	4.115-4.135	104.53-105.02	2.715	68.97	2.875	73.02	24.56	11.140
AS3255-41	4.240-4.260	107.70-108.20	2.840	72.14	3.000	76.20	25.19	11.427
AS3255-42	4.365-4.385	110.88-111.37	2.965	75.32	3.125	79.37	25.83	11.714
AS3255-43	4.490-4.510	114.05-114.55	3.090	78.49	3.250	82.55	26.47	12.006
AS3255-44	4.615-4.635	117.23-117.72	3.215	81.67	3.375	85.72	27.10	12.293
AS3255-45	4.740-4.760	120.40-120.90	3.340	84.84	3.500	88.90	27.75	12.585
AS3255-46	4.865-4.885	123.58-124.07	3.465	88.02	3.625	92.07	28.38	12.872
AS3255-47	4.990-5.010	126.75-127.25	3.590	91.19	3.750	95.25	29.02	13.164
AS3255-48	5.115-5.135	129.93-130.42	3.715	94.36	3.875	98.42	29.66	13.452
AS3255-49	5.240-5.260	133.10-133.60	3.840	97.54	4.000	101.60	30.60	13.744
AS3255-50	5.365-5.385	136.28-136.77	3.965	100.72	4.125	104.77	30.93	14.030
AS3255-51	5.490-5.510	139.45-139.95	4.090	103.89	4.250	107.95	31.58	14.324
AS3255-52	5.615-5.635	142.63-143.12	4.215	107.07	4.375	111.12	32.22	14.615
AS3255-53	5.740-5.760	145.80-146.30	4.340	110.24	4.500	114.30	32.85	14.900
AS3255-54	5.865-5.885	148.98-149.47	4.465	113.42	4.625	117.47	33.50	15.195
AS3255-55	5.990-6.010	152.15-152.65	4.590	116.59	4.750	120.65	34.14	15.485

AEROSPACE STANDARD

BOLT, MACHINE-DOUBLE HEX EXTENDED
WASHER HEAD, DRILLED, PD SHANK, SILVER PLATED
.5000-20 UNJF-3A

AS3255
SHEET 2 OF 3

REV.
A