


REV. B	FEDERAL SUPPLY CLASS 5310	
	RATIONALE	
AS9201	REVISED THREAD SPECIFICATION MIL-S-8879 TO AS8879; CLARIFIED MARKING NOTE AND ADDED MFG MARKING REQUIREMENTS; ADDED INSPECTION REQUIREMENT NOTE 10; CORRECTED TRUE POSITION CONTROL FEATURE DATUM REFERENCES TO AGREE WITH MS9201B, AND STANDARD UPDATED TO CURRENT SAE PRACTICE.	
	THE INITIAL SAE PUBLICATION OF THIS DOCUMENT WAS TAKEN DIRECTLY FROM U.S. MILITARY STANDARD MS9201B, NOTICE 1. THIS SAE STANDARD RETAINS THE SAME PART NUMBERS ESTABLISHED BY THE ORIGINAL MILITARY DOCUMENT.	
	ANY REQUIREMENTS ASSOCIATED WITH QUALIFIED PRODUCTS LISTS (QPL) MAY CONTINUE TO BE MANDATORY FOR DOD CONTRACTS. REQUIREMENTS RELATING TO QPL'S HAVE NOT BEEN ADOPTED BY THE SAE FOR THIS STANDARD AND ARE NOT PART OF THIS SAE DOCUMENT.	
		THIRD ANGLE PROJECTION
CUSTODIAN: SAE E-25		PROCUREMENT SPECIFICATION: NONE
		AEROSPACE STANDARD (R) NUT, PLAIN, HEXAGON, BOSS CONNECTION, SILVER PLATED, 347 CRES UNS S34700
AS9201 SHEET 1 OF 4		REV. B

SAENORM.COM : Click to view the full PDF of as9201b




FIGURE 1

TABLE 1 - PART NUMBERS AND DIMENSIONS

PART NUMBER	NOM TUBE OD	D - NOMINAL THREAD	AF	E MIN	AB
MS9201-02	.125	.3125-24UNJF-3B	.553 - .564	.623	.312 - .332
MS9201-03	.188	.3750-24UNJF-3B	.616 - .627	.694	.375 - .395
MS9201-04	.250	.4375-20UNJF-3B	.679 - .690	.766	.438 - .458
MS9201-05	.312	.5000-20UNJF-3B	.741 - .752	.836	.500 - .520
MS9201-06	.375	.5625-18UNJF-3B	.803 - .814	.907	.562 - .582
MS9201-07	.438	.6250-18UNJF-3B	.865 - .877	.978	.625 - .645
MS9201-08	.500	.7500-16UNJF-3B	.990 - 1.002	1.121	.750 - .770
MS9201-09	.562	.8125-16UNJ-3B	1.052 - 1.064	1.191	.812 - .832
MS9201-10	.625	.8750-14UNJF-3B	1.114 - 1.127	1.262	.875 - .895
MS9201-11	.688	1.0000-12UNJF-3B	1.301 - 1.314	1.475	1.000 - 1.020
MS9201-12	.750	1.0625-12UNJ-3B	1.364 - 1.377	1.547	1.062 - 1.082
MS9201-14	.875	1.1875-12UNJ-3B	1.489 - 1.502	1.690	1.188 - 1.208
MS9201-16	1.000	1.3125-12UNJ-3B	1.614 - 1.627	1.833	1.312 - 1.332
MS9201-18	1.125	1.5000-12UNJ-3B	1.800 - 1.814	2.045	1.500 - 1.520
MS9201-20	1.250	1.6250-12UNJ-3B	1.926 - 1.940	2.189	1.625 - 1.645
MS9201-24	1.500	1.8750-12UNJ-3B	2.176 - 2.190	2.474	1.875 - 1.895
MS9201-28	1.750	2.2500-12UNJ-3B	2.549 - 2.564	2.899	2.250 - 1.270
MS9201-32	2.000	2.5000-12UNJ-3B	2.799 - 2.814	3.185	2.500 - 2.520

TABLE 1 - PART NUMBERS AND DIMENSIONS (CONTINUED)

PART NUMBER	NOM TUBE OD	K	L MIN	P	T	J	APPROX. MASS LB/100
MS9201-02	.125	.209 - .229	.552	.110	.240	.042 - .052	1.25
MS9201-03	.188	.209 - .229	.615	.110	.240	.042 - .052	1.44
MS9201-04	.250	.240 - .260	.678	.125	.305	.042 - .052	1.92
MS9201-05	.312	.240 - .260	.740	.125	.340	.050 - .060	2.18
MS9201-06	.375	.256 - .276	.802	.133	.370	.050 - .060	2.56
MS9201-07	.438	.256 - .276	.865	.133	.405	.050 - .060	2.87
MS9201-08	.500	.302 - .322	.990	.157	.470	.057 - .067	4.04
MS9201-09	.562	.302 - .322	1.052	.157	.500	.057 - .067	4.24
MS9201-10	.625	.349 - .369	1.115	.180	.540	.057 - .067	5.45
MS9201-11	.688	.396 - .416	1.302	.204	.625	.065 - .075	8.79
MS9201-12	.750	.396 - .416	1.365	.204	.660	.065 - .075	9.37
MS9201-14	.875	.396 - .416	1.490	.204	.725	.065 - .075	10.45
MS9201-16	1.000	.396 - .416	1.615	.204	.790	.065 - .075	11.68
MS9201-18	1.125	.396 - .416	1.802	.204	.890	.065 - .075	13.47
MS9201-20	1.250	.396 - .416	1.928	.204	.960	.065 - .075	14.76
MS9201-24	1.500	.396 - .416	2.178	.204	1.095	.065 - .075	17.23
MS9201-28	1.750	.396 - .416	2.552	.204	1.295	.065 - .075	21.32
MS9201-32	2.000	.396 - .416	2.802	.204	1.425	.065 - .075	24.19

NOTES:

- MATERIAL: 347 CORROSION AND HEAT RESISTANT STEEL AMS 5646 (UNS S34700).
- SURFACE FINISH: SILVER PLATE PER AMS 2410; .0003-.0006 THICK ON THREAD AT PD. DIMENSIONS ARE AFTER PLATING.
- SURFACE TEXTURE: SYMBOLS PER ASME Y14.36M. REQUIREMENTS PER ASME B46.1. UNLESS OTHERWISE SPECIFIED, SURFACES TO BE 125 MICRONS Ra.
- BREAK EDGES .003 TO .015 UNLESS OTHERWISE SPECIFIED.
- DIMENSIONING AND TOLERANCING PER ANSI Y14.5M-1982 (ASME PUBLICATION).
- MARKING: MARK MATERIAL CODE "EH5" AS SHOWN PER AS269 IN ACCORDANCE WITH AS478, CLASS C. MULTIPLE MARKING OF BAR STOCK PERMISSIBLE, I.E., DUPLICATION OF WHOLE OR PART OF SYMBOL OR OFFSET OF SYMBOL SUCH THAT UPPER PORTION APPEARS BELOW LOWER PORTION ON FINISHED PART IS PERMISSIBLE, PROVIDED POSITIVE IDENTIFICATION IS SHOWN. PARTS MANUFACTURED AFTER MAY 1, 2006 SHALL BE MARKED WITH THE MANUFACTURERS IDENTIFICATION DEPRESSED .010 MAXIMUM PER AS478 CLASS A. PARTS SHALL BE MARKED BEFORE THREADING.
- DIMENSIONS ARE IN INCHES.
- DO NOT USE UNASSIGNED PART NUMBERS.
- THE CHANGE BAR (I) LOCATED IN THE LEFT MARGIN IS FOR THE CONVENIENCE OF THE USER IN LOCATING AREAS WHERE REVISIONS, NOT EDITORIAL CHANGES, HAVE BEEN MADE TO THE PREVIOUS ISSUE OF THIS DOCUMENT. AN (R) SYMBOL TO THE LEFT OF THE DOCUMENT TITLE INDICATES A COMPLETE REVISION OF THE DOCUMENT.