

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

AS9502

FEDERAL SUPPLY CLASS
5306

NOTICE


THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MS9502A, AMENDMENT 1, NOTICE 1 AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MS9502A, AMENDMENT 1, NOTICE 1. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS SAE TECHNICAL DOCUMENT.

SAENORM.COM : Click to view the full PDF of as9502

THIRD ANGLE PROJECTION



ISSUED 1999-08

PREPARED BY SAE COMMITTEE E-25

PROCUREMENT SPECIFICATION: NONE

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space®
INTERNATIONAL
400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD

BOLT, MACHINED - HEXAGON HEAD, DRILLED, 1 HOLE,
FULL SHANK, AMS 5731, .3125-24 UNJF-3A

AS9502
SHEET 1 OF 3

Copyright 1999 Society of Automotive Engineers, Inc.
All rights reserved.

Printed in the U.S.A.

QUESTIONS REGARDING THIS DOCUMENT: (724) 772-8510
TO PLACE A DOCUMENT ORDER: (724) 776-4970

FAX: (724) 776-0243
FAX: (724) 776-0790

SAE WEB ADDRESS: <http://www.sae.org>

MARK PART NUMBER AND MANUFACTURER'S IDENTIFICATION PER AS 478 CLASS A

.561 MIN

.502
.492

.198
.182

K

.127
.113

.016

.025 R
.015

MAXIMUM 2 INCOMPLETE THREADS (SEE NOTE 4)

CHAMFER .047 x 45° APPROX

.060-.070 DIA CSK 90° TO .100 DIA BOTH ENDS

.312
.309 DIA

.3125-24 UNJF-3A MIL-S-8879

A

THIS SURFACE MUST BE SQUARE WITH SHANK WITHIN .003 FIR

CHAMFER 30° TO .500 DIA

.460 DIA MIN BEARING SURFACE

.510 DIA MAX

VIEW A ENLARGED

SECTION THRU THREAD PROFILE

PART NUMBER	L	K	APPROX WEIGHT LB/100	PART NUMBER	L	K	APPROX WEIGHT LB/100
MS9502-04	.500	.088-.108	2.15	MS9502-31	2.625	1.690-1.750	6.75
MS9502-05	.562	.088-.108	2.29	MS9502-32	2.750	1.815-1.875	7.03
				MS9502-33	2.875	1.940-2.000	7.30
				MS9502-34	3.000	2.065-2.125	7.57
				MS9502-35	3.125	2.190-2.250	7.80
MS9502-06	.625	.088-.108	2.42	MS9502-36	3.250	2.315-2.375	8.11
MS9502-07	.688	.088-.108	2.56	MS9502-37	3.375	2.440-2.500	8.38
MS9502-08	.750	.088-.108	2.70	MS9502-38	3.500	2.565-2.625	8.65
MS9502-09	.812	.088-.108	2.83	MS9502-39	3.625	2.690-2.750	8.92
MS9502-10	.875	.088-.108	2.97	MS9502-40	3.750	2.815-2.875	9.19
MS9502-11	.938	.088-.108	3.10	MS9502-41	3.875	2.940-3.000	9.46
MS9502-12	1.000	.088-.125	3.24	MS9502-42	4.000	3.065-3.125	9.73
MS9502-13	1.062	.128-.188	3.37	MS9502-43	4.125	3.190-3.250	10.00
MS9502-14	1.125	.190-.250	3.51	MS9502-44	4.250	3.315-3.375	10.27
MS9502-15	1.188	.252-.312	3.64	MS9502-45	4.375	3.440-3.500	10.54
MS9502-16	1.250	.315-.375	3.78	MS9502-46	4.500	3.565-3.625	10.81
MS9502-17	1.312	.378-.438	3.91	MS9502-47	4.625	3.690-3.750	11.08
MS9502-18	1.375	.440-.500	4.05	MS9502-48	4.750	3.815-3.875	11.36
MS9502-19	1.438	.502-.562	4.18	MS9502-49	4.875	3.940-4.000	11.63
MS9502-20	1.500	.565-.625	4.32	MS9502-50	5.000	4.065-4.125	11.90
MS9502-21	1.562	.628-.688	4.45	MS9502-51	5.125	4.190-4.250	12.17
MS9502-22	1.625	.690-.750	4.59	MS9502-52	5.250	4.315-4.375	12.44
MS9502-23	1.688	.752-.812	4.73	MS9502-53	5.375	4.440-4.500	12.71
MS9502-24	1.750	.815-.875	4.86	MS9502-54	5.500	4.565-4.625	12.98
MS9502-25	1.875	.940-1.000	5.13	MS9502-55	5.625	4.690-4.750	13.25
MS9502-26	2.000	1.065-1.125	5.40	MS9502-56	5.750	4.815-4.875	13.52
MS9502-27	2.125	1.190-1.250	5.67	MS9502-57	5.875	4.940-5.000	13.78
MS9502-28	2.250	1.315-1.375	5.94	MS9502-58	6.000	5.065-5.125	14.06
MS9502-29	2.375	1.440-1.500	6.21	MS9502-59	1.812	.878-.938	5.00
MS9502-30	2.500	1.565-1.625	6.48	MS9502-60	1.938	1.002-1.062	5.27