



400 Commonwealth Drive, Warrendale, PA 15096-0001

SURFACE VEHICLE STANDARD

SAE J1026

REV.
APR90Issued 1973-07
Revised 1990-04-17

Superseding J1026

Submitted for recognition as an American National Standard

BRAKE PERFORMANCE – CRAWLER TRACTORS AND CRAWLER LOADERS

1. SCOPE:

This SAE Standard applies to crawler tractors and crawler loaders as identified in SAE J1057 and SAE J1116 and having a manufacturer's maximum specified speed of 16 km/h.

1.1 Purpose:

To provide performance criteria for service brake systems, secondary brake systems, and parking brake systems for crawler tractors and crawler loaders.

2. REFERENCES:

2.1 Applicable Documents:

SAE J727, Nomenclature – Crawler Tractor

SAE J732, Specification Definitions – Loaders

SAE J742, Capacity Rating – Loader Bucket

SAE J818, Rated Operating Load for Loaders

SAE J1057, Identification Terminology of Earthmoving Machines

SAE J1116, Categories of Off-Road Self-Propelled Work Machines

SAE Technical Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

SAE J1026 Revision APR90

2.2 Definitions:

- 2.2.1 CRAWLER TRACTOR: Crawler tractor is defined in SAE J1057 and is illustrated with parts nomenclature in SAE J727. The tractor may, in addition, have any combination of attachments mounted on it that are formally approved by the machine manufacturer.
- 2.2.2 CRAWLER LOADER: Crawler loader is defined in SAE J1057 and SAE J732. The loader may have any type of bucket or other tool, and any other combination of mounted attachments that are formally approved by the machine manufacturer.
- 2.2.3 BRAKE SYSTEMS: All the components which participate in stopping and holding the machine. Such systems consist of a control, means of power transmission, and the brake itself.
- 2.2.3.1 Service Brake System: The primary system used for stopping and holding the machine.
- 2.2.3.2 Secondary Brake System: The system used for stopping the machine in the event of any single failure in the service brake system.
- 2.2.3.3 Parking Brake System: The system used to hold a stopped machine in a stationary position.
- 2.2.3.4 Common Component: A component that performs a function in two or more brake systems.
- 2.2.4 BRAKE(S): The component which directly applies a force to oppose movement of the machine. Brakes may, for example, be friction, electrical, or fluid types.
- 2.2.5 SLIDE: Slide, as used in this criterion, is defined as no track rotation during machine movement.
- 2.2.6 MACHINE MASS: Crawler Tractor - Operating mass of the machine up to the mass of the heaviest combination of equipment approved by the manufacturer of the machine, an operator of 75 kg, and with the machine fully fueled and serviced.
- 2.2.7 MACHINE MASS: Crawler Loader - Operating mass of the machine up to the mass of the heaviest combination of equipment approved by the manufacturer of the machine, a loaded bucket per SAE J742 not to exceed rated load as defined in SAE J818, an operator of 75 kg, and with the machine fully fueled and serviced.
- 2.2.8 BRAKE FORCE: Decelerating force due to the brake system, plus rolling resistance, but it does not include engine torque.

3. BRAKE SYSTEM PERFORMANCE:

3.1 Common Component:

The brake systems may use common components. However, a failure of any single component, or a failure of any single common component, shall not reduce the effectiveness of the machine's stopping capability to less than the secondary stopping performance, as defined in 3.3.1.

3.2 Service Brake System:

The machine shall have a service brake system.

3.2.1 Brake Performance: The service brake system is tested by towing. The service brake system when fully applied on a machine moving in either forward or reverse shall cause the tracks to slide or develop a brake force in Newtons equal to 9.8 times the operating mass in kilograms.

3.3 Secondary Brake System: The machine shall have a secondary brake system capable of being applied by a person seated in the operator's seat. It also may be applied automatically.

3.3.1 Brake Performance: The secondary brake system is tested by towing. The secondary brake system when fully applied on a machine moving in either forward or reverse shall cause at least one track to slide or develop a brake force in Newtons equal to 3.8 times the operating mass in kilograms.

3.3.2 Secondary Brake System Release: The secondary brake system shall be arranged so that it cannot be released from the operator's seat unless immediate reapplication can be made from the operator's seat to meet the requirements of 3.3.1.

3.4 Parking Brake System:

The machine shall have a parking brake system capable of being applied and released by a person seated in the operator's seat. It also may be applied automatically.

3.4.1 Parking Brake System Performance: The parking brake system when fully applied in either the forward or reverse direction shall either hold the tracks stopped on any incline on which the machine (and towed load if applicable) is operating unaided or develop a static brake force in Newtons equal to 6.5 times the mass of the unit in kilograms if the parking brake system is tested by pulling a parked machine.

3.4.2 Remain Applied: The parking brake system while applied shall maintain the parking brake performance in compliance with 3.4.1 despite any contraction of the brake parts or leakage of any kind. This system shall not be dependent upon an exhaustible energy source.

- 3.4.3 The failure of a common component may prevent the application of the parking brake system.

3.5 Control Forces:

Control forces needed to meet the required brake performance for the systems defined in Section 4 shall not exceed the values in Table 1:

TABLE 1

Control Types	Force
Finger grasp (flip levers and switches)	20N
Hand grasp	
Upwards	400N
Fore-aft	300N
Sideways	300N
Foot Pedal (leg control)	700N
Foot Treadle (ankle control)	350N

4. BRAKE TEST CRITERIA:

4.1 Facilities:

- 4.1.1 A level (within 3% slope) test course of adequate size to conduct the test described in 3.2.1. The soil conditions of the test course should be similar to those in which the machine is operating. If these soil conditions are not available, it is recommended that the soil be of the type that contains not less than 10% clay, not more than 70% sand, and not less than 10% silt. This foregoing statement is to be used as a guideline only and is not meant to imply that a laboratory soil analysis test is required. Moisture content of the soil shall be such that the mass of the test machine can be supported with only nominal sinkage.
- 4.1.2 A test course for the self-propelled machine with adequate grades to simulate the conditions in 3.4.1. If a towing test is to be conducted, the course shall be level, as in 4.1.1.
- 4.1.3 A means of providing the force required to complete the test conditions outlined in 3.2.1, 3.3.1, and 3.4.1.

4.2 Instrumentation:

4.2.1 A means to measure and record the following parameters within the specified accuracy:

Parameter	Accuracy
Brake System Pressure	$\pm 3.0\%$
Machine Mass	$\pm 2.5\%$
Brake Control Actuating Force	$\pm 3.0\%$
Grade	$\pm 1.0\%$
Brake Force	$\pm 3.0\%$

4.3 Test Requirements:

4.3.1 The service and secondary brake performance tests are to be run by towing the machine at a speed of 2 to 5 km/h to reduce the effects of frictional drag. The transmission of the test machine shall be in neutral or in the brake position.

NOTE: Some machines are designed to automatically apply the brake system(s) when the transmission control is in the neutral position (hydrostatic drive, etc.). These machines may be tested by driving at the same speed as the towing machine, then apply the brake system(s) being tested by placing the appropriate control in the brake position.

J1026 APR90RATIONALE:

SAE J1026 has been reviewed to satisfy the five year update requirements for SAE documents. No changes in the performance requirements have been made, except for the allowable brake actuation force.

The Purpose and Scope have been rewritten to reflect the current meaning of these sections.

The Definitions section now includes what was previously Identification and Definitions.

All reference to English units have been deleted.

Control Force requirements have been consolidated into one section, 3.5. They have been specified to be consistent with values of current SAE J documents.

Instrumentation Accuracy is grouped into one section, 4.2.1. Values are consistent with current SAE J documents.

RELATIONSHIP OF SAE STANDARD TO ISO STANDARD:

Not applicable.

APPLICATION:

This SAE Standard applies to crawler tractors and crawler loaders as identified in SAE J1057 and SAE J1116 and having a manufacturer's maximum specified speed of 16 km/h.

REFERENCE SECTION:

SAE J727, Nomenclature - Crawler Tractor

SAE J732, Specification Definitions - Loaders

SAE J742, Capacity Rating - Loader Bucket

SAE J818, Rated Operating Load for Loaders

SAE J1057, Identification Terminology of Earthmoving Machines

SAE J1116, Categories of Off-Road Self-Propelled Work Machines

COMMITTEE COMPOSITION:DEVELOPED BY THE SAE ORMTC SC10 - BRAKING:

S. L. Kershaw, Caterpillar Inc., Decatur, IL - Chairman

J. A. Kaltenbach, VME Americas Inc., Cleveland, OH - Vice Chairman

S. K. Brown, Ingersoll-Rand, Shippensburg, PA

W. L. Daniels, Sr., BF Goodrich Co., Bloomington, IN

G. E. Danner, Rockwell Int'l., Troy, MI

J. F. Dernovshek, Rockwell Int'l., York, SC

W. T. Fouser, Hyster Co., Kewanee, IL

A. Green, Barber Greene Co., DeKalb, IL