

	SURFACE VEHICLE RECOMMENDED PRACTICE		J1765 JUN2012
		Issued	1995-05
		Stabilized	2012-06
		Superseding J1765 AUG2011	
SAE Miniature Bulb Vibration Test			

RATIONALE

SAE J1765 will be stabilized at this time because no further changes to the procedures or requirements are foreseen in the near future after the August 2011 updates were made. If proposed changes come up the document will be opened for review.

STABILIZED NOTICE

This document has been declared "Stabilized" by the SAE Test Methods and Equipment Standards Committee and will no longer be subjected to periodic reviews for currency. Users are responsible for verifying references and continued suitability of technical requirements. Newer technology may exist.

SAENORM.COM : Click to view the full PDF of J1765_201206

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2012 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
 Tel: +1 724-776-4970 (outside USA)
 Fax: 724-776-0790
 Email: CustomerService@sae.org
 SAE WEB ADDRESS: <http://www.sae.org>

**SAE values your input. To provide feedback
 on this Technical Report, please visit
http://www.sae.org/technical/standards/J1765_201206**

1. SCOPE

This SAE Recommended Practice was designed to be an accelerated vibration test that subjects bulbs to critical vibration/shock loading typically observed in normal vehicle service and can be employed for conformance of production (COP) testing. The test was designed for external vehicle applications.

2. REFERENCES

2.1 Applicable Document

The following publication forms a part of this specification to the extent specified herein. Unless otherwise indicated, the latest issue of SAE publications shall apply.

2.1.1 SAE Publication

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or 724-776-4970 (outside USA), www.sae.org.

SAE J573 Miniature Lamp Bulbs

SAENORM.COM : Click to view the full PDF of J1765 - 201206

2.2 Related Publications

The following publications are provided for information purposes only and are not a required part of this SAE Technical Report.

2.2.1 SAE Publication

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or 724-776-4970 (outside USA), www.sae.org.

SAE J1455 Recommended Environmental Practices for Electronic Equipment Design in Heavy-Duty Vehicle Applications

2.2.2 FMVSS Publication

Available from the National Highway Traffic Safety Administration, 400 Seventh Street SW, Washington, DC 20024-0002, www.access.gpo.gov/nara/cfr/cfr-table-search.html#page1.

FMVSS108 Lamps, Reflective Devices, and Associated Equipment (Available as 49 CFR 571.108)

2.2.3 IEC Publication

Available from American National Standards Institute, 25 West 43rd Street, New York, NY 10036-8002, Tel: 212-642-4900, www.ansi.org or www.IEC.com.

IEC 810 Lamps for Road Vehicles—Performance Requirements

3. DEFINITIONS

3.1 POWER SPECTRAL DENSITY (PSD)

The product of the real and imaginary Fourier coefficients of a signal divided by the frequency interval. The square root of the integral of PSD over all measured frequencies will yield the root-mean-square acceleration (G_{rms}).

3.2 WIDE BAND RANDOM

Random vibration whose power spectral density has a relatively broad frequency range. All frequencies in the test range are excited simultaneously as opposed to the "narrow-band" where only a small portion of the frequencies in the test frequency range are excited at any one time.

3.3 FILAMENT MOUNT STRUCTURE

The filament mount structure consists of the filament, electrical lead wires, clamps or welds, and any filament or lead supports that comprise the active structure inside the bulb.

3.4 CLOSED-LOOP DYNAMIC VIBRATION EQUIPMENT

A laboratory test system consisting of an electromagnetic exciter (shaker), a feedback transducer (accelerometer), and a control unit with necessary power amplifiers capable of reproducing, within prescribed statistical limits, a predetermined vibration profile for the purpose of performing environmental stress screening. Figure 1.

3.5 NATURAL FREQUENCY

A vibration frequency of a mechanical system when the system is allowed to freely oscillate following an initial displacement. Real mechanical systems have numerous natural frequencies corresponding to distinct natural modes of vibration. Natural frequencies are inherent properties of a mechanical system, determined by the distribution of mass and stiffness of the system, and by boundary conditions imposed upon the system.

3.6 RESONANT FREQUENCY

A frequency at which the ratio of the steady-state response amplitude (at the point of excitation) to harmonic excitation magnitude reaches a relative maximum. Resonant frequencies closely (but not necessarily exactly) coincide with natural frequencies.

Resonant frequencies are dependent upon the type and location of harmonic excitation (e.g., force, displacement, or velocity), as well as the mechanical properties and boundary conditions of the mechanical system. For example, displacement resonance and velocity resonance occur at different frequencies for any system with damping. (Ordinarily the difference is not significant.) A system will not exhibit a resonant frequency corresponding to a particular natural frequency if the point of excitation is at a node of the modeshape for the natural frequency; however, an antiresonance will be exhibited at that frequency (i.e., zero vibration amplitude at the point of excitation).

3.7 G_{rms}

The root-mean-square acceleration equivalent as a ratio with respect to gravity.

4. USAGE

4.1 Bulbs identified for use in vehicle exterior applications, typical bulb listing in SAE J573, shall meet this document.

5. TEST PROCEDURE

5.1 Seasoning

Bulbs are seasoned as specified in SAE J573 prior to being subjected to testing.

5.2 Voltage

Test shall be conducted at the voltage specified in SAE J573 or as specified by the manufacturer.

5.3 Test Equipment

The test equipment shall be closed-loop dynamic vibration equipment and controller (or equivalent) capable of vibrating in random modes, produce variable vibration from 10 to 2000 Hz with a tolerance of ± 4 dB and a minimum of 500 lb force.

5.4 Test Fixture Mounting

The bulb shall be fastened rigidly to a fixture on the vibration table. This may be achieved by clamping, soldering, or embedding. Electrical connections shall be made such that the connection is assured during the whole test.

Fixtures shall be designed and verified such that their natural frequencies (fully loaded or unloaded) do not occur below 1200 Hz, in the appropriate test axis.

5.5 Control Point

Attach the transducer used to measure and maintain the specified vibration characteristics at a control point location as close to the test bulb as possible on the test fixture without interfering with the bulb resonance frequencies.

5.6 Axis of Vibration

With the filament mounting structure horizontal, a direction of excitation normal to the filament(s) axis is used for testing.