

HOLES IN BOLT AND SCREW SHANKS AND SLOTS IN NUTS FOR COTTER PINS

1. **Scope**—SAE J485 specifies the recommended nominal diameters and locations of holes in bolt or screw shanks, and nominal widths and depths of slots in nuts, for use with the recommended sizes of inch-series cotter pins, as shown in Table 1.

TABLE 1—DIMENSIONS FOR COTTER PIN HOLES AND SLOTS (all dimensions are in inches)

Bolt, Screw, and Nut Nominal Size	Bolt, Screw, and Nut Nominal Size	Hole in Bolt or Screw Shank Dia ⁽¹⁾	Hole in Bolt or Screw Shank Distance, Extreme Point of Bolt or Screw to Hole Center ⁽²⁾	Slot in Nut ⁽³⁾ Width ⁽⁴⁾	Slot in Nut ⁽³⁾ Depth ⁽⁴⁾	Cotter Pin ⁽⁵⁾ Nominal Size	Cotter Pin ⁽⁵⁾ Nominal Size	Cotter Pin ⁽⁵⁾ Min	Cotter Pin ⁽⁵⁾ Max
1/4	0.250	0.078	0.109	0.078	0.094	1/16	0.062	0.056	0.060
5/16	0.3125	0.094	0.109	0.094	0.094	5/64	0.078	0.072	0.076
3/8	0.375	0.109	0.141	0.125	0.125	3/32	0.094	0.086	0.090
7/16	0.4375	0.109	0.172	0.125	0.156	3/32	0.094	0.086	0.090
1/2	0.500	0.141	0.172	0.156	0.156	1/8	0.125	0.116	0.120
9/16	0.5625	0.141	0.203	0.156	0.188	1/8	0.125	0.116	0.120
5/8	0.625	0.172	0.234	0.188	0.219	5/32	0.156	0.146	0.150
3/4	0.750	0.172	0.266	0.188	0.250	5/32	0.156	0.146	0.150
7/8	0.875	0.172	0.281	0.188	0.250	5/32	0.156	0.146	0.150
1	1.000	0.203	0.312	0.250	0.281	3/16	0.188	0.172	0.176
1-1/8	1.125	0.203	0.391	0.250	0.344	3/16	0.188	0.172	0.176
1-1/4	1.250	0.234	0.406	0.312	0.375	7/32	0.219	0.202	0.207
1-3/8	1.375	0.234	0.438	0.312	0.375	7/32	0.219	0.202	0.207
1-1/2	1.500	0.266	0.484	0.375	0.438	1/4	0.250	0.220	0.225
1-5/8	1.625	0.266	0.484	0.375	0.438	1/4	0.250	0.220	0.225
1-3/4	1.750	0.312	0.547	0.438	0.500	5/16	0.312	0.275	0.280
1-7/8	1.875	0.312	0.547	0.438	0.562	5/16	0.312	0.275	0.280
2	2.000	0.312	0.641	0.438	0.562	5/16	0.312	0.275	0.280
2-1/4	2.250	0.312	0.641	0.438	0.562	5/16	0.312	0.275	0.280
2-1/2	2.500	0.375	0.750	0.562	0.688	3/8	0.375	0.329	0.335
2-3/4	2.750	0.375	0.750	0.562	0.688	3/8	0.375	0.329	0.335
3	3.000	0.500	0.750	0.625	0.750	1/2	0.500	0.467	0.473

1. Required tolerances are to be specified on the drawing.
2. This dimension is suggested to determine the distance from the cotter pin hole to the bearing face of the bolt or screw head. The drawing should specify the length, with required tolerances or limits, from the under head bearing face to the hole center.
3. See ASME B18.2.2 for dimensions of standard slotted hex nuts, slotted heavy hex nuts, or slotted hex thick nuts.
4. This dimension is suggested to determine the nut unslotted thickness, the distance from the nut bearing face to the bottom of the slots. The drawing should specify the nut unslotted thickness with required tolerances or limits.
5. See ASME B18.8.1 for dimensions of standard cotter pins.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

TO PLACE A DOCUMENT ORDER; (724) 776-4970 FAX: (724) 776-0790
SAE WEB ADDRESS <http://www.sae.org>

2. **References**

2.1 Applicable Publications—The following publications form a part of this specification to the extent specified herein.

2.1.1 ASME PUBLICATIONS—Available from ASME, 22 Law Drive, Fairfield, NJ 07007-2900.

ASME B 18.2.2—Square and Hex Nuts (Inch Series)

ASME B 18.8.1—Clevis Pins and Cotter Pins (Inch Series)

PREPARED BY THE SAE FASTENERS COMMITTEE

SAENORM.COM : Click to view the full PDF of J485 - 199805